



Speaker type	12" forward-firing composite cone woofer, 3" voice coil
Xmax	20 mm excursion each direction (40 mm linear), voice coil remaining in homogeneous magnetic field, linear and lowest distortion
Passive   Active	Active, built in DSP Amplifier
Prinziple	Vented
Frequency range	Calculated data 30 Hz - 150 Hz
Directivity horizontal x vertical in Deg°	360°
Output power	600 W
Power voltage range	110 V or 220 V / switchable
Input sensivity	1 V / 20 KΩ
LFE input	1 x XLR balanced
Line level input	2 x RCA / unbalanced
LFE output	1 x XLR balanced
Line level output	2 x RCA / unbalanced
Features	LP crossover 40 Hz to 150 Hz variable, phase 0° - 180°, volume control, auto turn on/off
Protection features	Therminal protection

Enclosure	Internally braced medium density fiber-board (MDF)
Width	15,75 "   400 mm
Hight	18,90 "   480 mm
Hight with feet	19,29 "   490 mm
Depth	15,75 "   400 mm
Depth with plug	18,11 "   460 mm
Weight	48,5 lbs   22 kg
Grille	Black acoustic fabric
Finish	Black ash
Custom colour options	Piano lacquer, colour of choice, matt or other finishes upon request
Shape customization	Upon request
Mounting	Floor standing with feet

