

**THE 6 PRO
PASSIVE
ON WALL**



Speaker type	6,5" Time coherent point-source coaxial
Passive Active	Passive
Enclosure type	Vented
SPL	Calculated data 112 dB cont. / 122 dB peak
Frequency Range	Calculated data 100 Hz - 20 kHz / -3dB
Sensitivity	94 dB / 1W/m
Power handling	200 W
Impedance	8 Ω
Woofer	6.5" woofer, cone from graphene carbon non woven mix
Tweeter Hochtöner	1" soft dome tweeter with presence EQ switch 0dB +3dB
Directivity horizontal x vertical in Deg°	85° x 85°
Input Terminal	One 4-conductor Phoenix 12 AWG (3,3 mm²) push on binding post
Enclosure Gehäuse	Aluminum MDF damped sandwich

Width	10,49" 266,5 mm
Height	17,58" 446,5 mm
Depth (with grille)	3,94" 100 mm
Depth (without grille)	3,66" 93 mm
Depth grille	0,28" 7 mm
Weight	16,53 lbs 7,5 kg
Finish	Brushed aluminum black anodized
Mounting	4 x wall brackets for horizontal and vertical installation + VESA 200 x 100 mounting points

The THE6 PRO PASSIVE ON WALL is supplied with a front cover as standard

