3G ULTRA 717HIFI Transmitter

VBS-HDIP-717HIFI

All Audio Capable with HDMI Loop-out Transmitter

The 3G Ultra 717HIFI Transmitter supports lossless audio formats and has an HDMI loop-out, along with all the 4K system wide features from the 3G Ultra product line.

Distribute 4K video and lossless audio over a single Cat5e cable to every zone.

Build a future-proof 4K infrastructure.

The 717HIFI encodes a 4K or lower-resolution source device into an IP signal and sends it over the network with ultra-low latency and instant switching; supports HDCP 2.2; and features image pull and RS-232, IR, and CEC control of sources.

Features

| Audio | All lossless audio supported - including Dolby Atmos ® | Image Pull | Preview an image from any source or display in any web browser or control system - up to 10 fps |
|------------------|--|--------------------------------|--|
| HDCP 2.2 Support | Display content with HDCP 2.2 copy/content protection on any HDMI screen in system | Integrated Endpoint Control | Control endpoints with RS232, IR and CEC |
| | | Scalability | Fully compatible with all 3G Ultra and 2G Omega products |





3G ULTRA 717HIFI Transmitter VBS-HDIP-717HIFI

Front of Device:



All measurements in millimeters (mm)

Back of Device:



All measurements in millimeters (mm)

Specifications

| Bandwidth | 180-500 Mbps | POE | 10 watts maximum |
|---------------------|--|--------------------------------|---|
| Compliance | HDCP 2.2 RoHS/FCC/CE | Ports | Gigabit Ethernet HDMI In HDMI Out |
| Dimensions & Weight | 184 x 30 x 126 mm 7.2" x 1.2" x 5.0" in | | 3.5mm RS232 w/null modem |
| | 0.45 kg / 1.0 lb | Power Supply (not included) | ~4.7-23V 5.5mm/2.1mm, Positive tip |
| Encryption | Hardware-Based AES 256-bit Encryption of network video signal | (, | |
| | | Supported Resolutions | Up to 4096x2160 (interlaced & progressive) |
| Operating Temp | 0-60 °C / 32-140 °F | | |