

THE **12**  
PASSIVE  
ON WALL



Speaker type	12" Time coherent point-source coaxial
Passive   Active	Passive
Enclosure type	Vented
SPL	Measurement data 122 dB cont. / 132 dB peak
Frequency Range	Measurement data 95 Hz - 20 kHz / -3dB
Sensitivity	99 dB / 1W/m
Power handling	600 W
Impedance	8 Ω
Woofer	12" Woofer featuring lightweight paper cone and high-power long throw magnet system
Tweeter   Hochtöner	1,75" Compression driver
Directivity horizontal x vertical in Deg°	85° x 85°
Input Terminal	One 4-conductor Phoenix 12 AWG (3,3 mm²) push on binding post
Enclosure   Gehäuse	MDF

Width	15,35"   390 mm
Height	24,21"   615 mm
Depth with plug	6,89"   175 mm
Depth with grille	7,24"   184 mm
Depth grille	0,35"   9 mm
Weight	47,4 lbs   22,0 kg
Finish	Matte black
Custom colour options	Piano lacquer: colour of choice, matt or other finishes upon request, color of choice
Shape customization	Upon request   Auf Anfrage
Mounting	4 x wall brackets for horizontal and vertical installation + VESA 200 x 100 mounting points

The THE12 PASSIVE ON WALL is supplied with a front cover as standard



Technical modifications subject to change without further notice | Technische Änderungen vorbehalten