



SPECIFICATIONS

Woofer	5" Poly Cone
Tweeter	¾" Titanium Dome
Power Handling	80W RMS, 200W Peak into 16 ohm
Nominal Impedance	16
Frequency Response	85 Hz - 20 kHz
Crossover Frequency	2.5 kHz
Sensitivity 2.83 V / 1 Meter	87
Tap Settings	30W, 15W, 7.5W, 3.75W, 16 ohm
Connections	Removable screw-terminal
Weight	6.9 lbs.
Cut-out Dimensions	8.3"
Finish Dimensions	9.5" diameter, 8.6" D
Mounting Depth	8.2"

OVERVIEW

When you are searching for a great sounding commercial speaker that is easy to install, look no further than the ES-600C-IC-5. Improved components, crossovers, front tap and included tile bridges make these commercial speakers an installer's dream. Add amazing sound quality and a lifetime warranty, and you're looking at a "best-in-class" product for commercial applications.

FEATURES

- Front-mounted switch for easy tap adjustments after installation
- Extended low frequency response with optimally tuned and ported steel enclosure
- Pivoting tweeter provides installation versatility and precise tuning
- Easy installation in drop tile or sheetrock ceilings with "dog toggle" mounting system and included tile bridge
- Protective rear cover with knock-outs allows through-conduit installation
- Security hook for attachment to ceiling grid
- Removable screw-terminal connector with loop out for easy wire terminations and speaker connections
- Aluminum grilles and plastic bezel improve aesthetics for a contemporary look
- High-quality transformers minimize insertion loss while delivering increased power handling for demanding audio applications
- Self-resetting poly-switch offers increased protection in high output situations
- ETL Listed. Complies with UL-1480 and UL-2043 standards

