SILVER SATELLITE

IN-ROOM, IN-CEILING, IN-WALL



SILVER SATELLITE

IN-ROOM, IN-CEILING, IN-WALL

The Triad Silver Satellite's 6" drivers, high-fidelity sound, and extended bass response makes it ideal for multiroom audio, mid-sized surround sound systems, home theaters, and media rooms. Paired with high-power AVRs, it produces rich audio that will immerse large areas with dynamic acoustics at forefront and background listening levels. With premium components and a two-way compact design, the Silver Sat delivers precise sound reproduction and isolation.

In an industry of generic, mass-produced products, Triad combines craftsmanship and customization in every order. Handcrafted in the US using the finest materials and components, Triad's fully engineered, sealed, and internally braced MDF enclosures deliver intricate acoustics and effortless playback, achieving unobtrusive elegance while retaining the integrity of sound. Use as a capable, standalone pair of speakers, or create a full-range sound experience by pairing with Triad LCRs and subs.

The Silver Sat duplicates sound with minimal alteration and interference, subtly transporting its listeners. Serving both your practical and acoustic needs, Triad's Silver Sat speakers complement your space while producing a lifelike soundstage.

FEATURES

- Compact, two-way design
- Fully engineered, premium MDF enclosure
- Acoustic suspension
- · Custom paint matching available
- Braced enclosure keeps sound from bleeding into adjacent rooms

IN-ROOM

- Cloth grill
- 3/8"-16 threaded insert
- Veneer finishes available

IN-CEILING

- · AcoustiPerf metal grill
- Recessed angled baffle directs sound to the listener

IN-WALL

AcoustiPerf metal grill



SILVER SATELLITE IN-ROOM, IN-CEILING, IN-WALL

C		\bigcirc I		CA	TI	NIC
\sim	\vdash	VΙ	ГΙ	\cup	ΛII	\sim

MATERIALS

IN-ROOM

IN-CEILING/6

IN-WALL/4

1" (25 mm)

Fabric dome

Tweeter count

Tweeter size 1" (25 mm)

Fabric dome

Woofer count Woofer size

Tweeter type

6 1/2" (17 cm) Paper/fiber blend Woofer type

1" (25 mm) Fabric dome

6 1/2" (17 cm)

6 1/2" (17 cm) Paper/fiber blend

Paper/fiber blend

PERFORMANCE

Recommended amplifier power

Impedance

Sensitivity (dB @ 2.83V, 1 m)

Peak output (measured, 1 m)

Frequency response (+/- 3 dB)

IN-ROOM

25 - 125W

8 ohm

85 dB

107 dB

80 Hz - 20 kHz

IN-CEILING/6

25 - 125W

8 ohm

86 dB

107 dB

88 Hz - 20 kHz

IN-WALL/4

25 - 125W

8 ohm 86 dB

107 dB

88 Hz - 20 kHz

DIMENSIONS

Cabinet specifications (L × W × D)

Hole cut out (L × W)

Frameless grill dimensions (L × W)

NCB size

Product weight (each)

IN-ROOM

 $12^{3/4} \times 7^{15/16} \times 7^{1/4}$ " $(32.4 \times 20.2 \times 18.4 \text{ cm})$

14 lb (6.4 kg)

Shipping weight (each)

IN-CEILING/6

 $13 \frac{1}{2} \times 13 \frac{1}{2} \times 5 \frac{15}{16}$ " $(34.3 \times 34.3 \times 15.1 \text{ cm})$

13 5/8 × 13 5/8" $(34.6 \times 34.6 \text{ cm})$

 $14^{13}/_{16} \times 14^{13}/_{16}$ " $(37.6 \times 37.6 \text{ cm})$

18 lb (8.2 kg)

20 lb (9.1 kg)

IN-CEILING/6

IN-WALL/4

 $16^{3}/_{8} \times 10^{3}/_{4} \times 3^{15}/_{16}$ " $(41.6 \times 27.3 \times 9.9 \text{ cm})$

 $16^{1/2} \times 10^{7/8}$ " $(41.9 \times 27.6 \text{ cm})$

12 ¹/₁₆ × 17 ⁵/₈"

 $(30.6 \times 44.8 \text{ cm})$

13 lb (5.9 kg)

16 lb (7.3 kg)

PRODUCT NUMBERS

Painted finish Veneer finish

Right side mounting

Left side mounting

IN-ROOM

25003-4000-2

25003-6000-2

16 lb (7.3 kg)

55503-1100-3

55503-1200-3

IN-WALL/4

45403-1000-3

DIMENSIONS







triadspkrs.co/

IN-ROOM

12 ³/₄" [32.4 cm]



IN-CEILING/6



IN-WALL/4

