



Speaker type	Time coherent 15" coax point-source
Principle	Vented
Passive Active	Active, 2Ch DSP + 2Ch amplifier are required
Recommended amplifiers	1 x low-mid amp channels with 85 Vrms, 120 Vpk, 10,6 A; high 44 Vrms, 62Vpk, 5,5 A; equivalent to LF 900W@8Ω, 1 x HF 240W@ 8Ω
SPL	Calculated data 128 dB cont. / 131 dB peak
Frequency range	Calculated data 65 Hz - 21 kHz / -3 dB
Woofers	15"
Tweeter	1,4" (Throat) compression driver
Directivity horizontal x vertical in Deg°	85° x 85°
Input terminal	Neutrik Speakon

Enclosure	Internally braced birch ply and MDF
Width	18,50" 470 mm
Height	34,25" 870 mm
Depth with plug	9,45" 240 mm
Depth without grill	9,45" 240 mm
Weight	69,45 lbs 31,5 kg
Finish	PU structural paint black
Custom colour options	Piano lacquer, colour of choice, matt or other finishes upon request
Shape customization	Upon request
Mounting	3 x wall brackets for horizontal and vertical installation + VESA 200 mounting points

The 15 PRO ACTIVE EXT is supplied with a front cover as standard

