

Titan Laser 37000 WU

37,000 ISO / 33,000 ANSI Lumens | Contrast Ratio: 18,000:1 (Dynamic Black) / 2,000:1 Native | Part Number: 119-704

TITAN LASER SERIES DIGITAL PROJECTORS



THE VISIONARIES CHOICE

37,000 ISO / 33,000 ANSI Lumens | Contrast Ratio: 18,000:1 (Dynamic Black) / 2,000:1 Native | Part Number: 119-704

Colour System:

Laser Phosphor

DMD Specification:

Display capability upto WUXGA

2.3 megapixels pixels on screen at WUXGA

Fast transit pixels for smooth greyscale and improved contrast.

Display resolutions WUXGA (1920 x 1200)

Aspect Ratio:

16x10

Fill Factor

87%

Display Type:

3 x 0.96" WUXGA DMD™

Key Features

Video & Graphics Processing

- DisplayPort 1.2
- 2 x HDMI 2.0b HDCP 2.2
- HDR processing
- 2 x HDMI 1.4b HDCP 1.4 for Dual Pipe processing and Frame Sequential 3D Format.
- Sequential Processing: 3D via single HDMI 1.4b input
- Dual Pipe Processing: 3D Left and Right eyes via two HDMI1.4b inputs.
- Synchronisation of active glasses.
- 3G-SDI with loop-through.
- DICOM simulation mode.
- DMX Art-Net

General Features

- Constant Brightness control
- Multi-Projector Brightness control
- Compatible with selected competitor lenses via lens converter
- Selectable EDID
- Custom Start-up Logo

Geometry Correction

- 4-Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, Arc and Image Rotation
- Non-linear warp
- Digital Zoom, Pan and Scan
- Blanking control for custom input window sizing.
- Scaling available for fixed aspect ratio screens.
- Unscaled processing for pixel mapped display

Edge Blending

- Blending control available for all sides with width control.
- Correction for non-active pixels at the edge of the display.
- Electronic Black Level Compensation.

Picture in Picture

- Two sources can be displayed simultaneously using 2D inputs. either picture in picture (PIP) , or side by side (PBP), with the original aspect ratios maintained.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable
- Allows projector to be placed up to 100m from source with low cost cabling
- Supports up to 4K UHD 3840 x 2160@60Hz 4:2:0 or 4K UHD 3840 x 2160@30Hz 4:2:2

Colour Processing

- Four colour modes available
- Powerful seven point colour correction for accurate colour matching with presets.
- Easy colour temperature selection
- Manual seven point colour adjustment

- Traditional lifts and gains

Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

Projector Automation

- Real-time clock provides daily on/off automation
- E-mail alerts for system status


Source Compatibility:

2D Graphics standards up to 4K-UHD 3840x2160 resolution at 60Hz via HDMI 2.0, HDBaseT (4:2:0), DisplayPort inputs

3D Graphics standards up to dual-pipe WUXGA 120Hz via HDMI 1.4b inputs

3G-SDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DisplayPort 1.2 (2D)	DisplayPort	1	3D Sync In	BNC	1
HDMI 1.4b (3D)	HDMI	2	3D Sync Out	BNC	1
HDMI 2.0b (2D)	HDMI	2	LAN	RJ45	2
3G-SDI in (2D)	BNC	1	RS-232	9-pin D-Sub	1
3G-SDI out	BNC	1	Wired Remote	3.5mm Stereo Jack	1
HDBaseT/LAN (2D)	RJ45	1	12V Trigger	3.5mm Stereo Jack	2
			3D Sync IR Out	BNC	1
3D Formats Supported			HDTV Formats Supported		
Sequential / 1080p @100Hz			1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)		
Sequential / 1080p @120Hz			1080i (50Hz, 60Hz)		
Sequential / WUXGA @100Hz (RB)			720p (50Hz, 60Hz)		
Dual -Pipe / 1080p @ 50Hz			2K (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)		
Dual -Pipe / 1080p @ 60Hz			4K-UHD (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)		
Dual -Pipe / WUXGA @ 50Hz (RB)					
Dual -Pipe / WUXGA @ 60Hz					
Computer Compatibility			Bandwidth		
2D 4K-UHD upto 60Hz			498 Mpixels/sec via DisplayPort and HDMI2.0.		
3D Supported Formats will be displayed upto WUXGA					
Remote Control			Automation Control		
Addressable IR remote Control, Wireless and wired. On-Board keypad			Crestron RoomView Connected		
			LAN		
			RS-232		
			AMX (Device Discovery)		
			DMX Art-Net		
			Served web pages (Projector status, Projector control, Crestron RoomView, Network settings, Alert mail setup, Time setup, Error log, On screen Display)		
Colour Temperature			Operation		
3200K to 9300K					
Illumination Type			Typical illumination Life		

Lenses

Lens	Part No.	Optimised Focus Range*	Lens Shift
0.37:1 (Right Angled)	120-510	1.6m - 4.9m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.3 (L) 0.3 (R) frame
0.65-0.85:1 (Right Angled)	120-511	2.8m - 8.4m	Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
0.8-1.16:1 (Includes support bracket)	120-827	1.7m - 11m	Vert: 0.4 (U) 0.4 (D) frame, Hor: 0.19 (L) 0.19 (R) frame
0.67:1 fixed HB	105-607	1.1m - 10m	Vert: 0.108 (U) 0.108 (D) frame, Hor: 0.044 (L) 0.044 (R) frame
1.12:1 (short) fixed HB	105-608	3m - 15m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.408 (U) 0.408 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame

* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,

Lens Mount

Motorised Shift, Zoom and Focus.(Lenses 0.67:1 & 1.12:1 have manual focus, shift is motorised)
Intelligent Lens Memory with 10 user-definable pre-set positions for zoom lenses.

Mechanical Mounting	Orientation
Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes
Power Requirements	Power Consumption
200VAC to 230VAC, 50/60Hz single phase	Typical: 3100W , Maximum 3400
Thermal Dissipation	Fan Noise
Max 11430 BTU/Hour @ 200VAC	Normal Mode: 50dBA, Max 52dBA Eco Typ: 47dBA
Operating/Storage Temperature	Operating Humidity
Operating: Full Power 0°C ~ 35°C (32°F ~95°F), ECO upto 40°C (104°F) Storage: -20°C ~ 60°C (-4°F ~ 140°F)	Operating: 10% ~ 90% non-condensing Storage: 10% ~ 90% non-condensing
Weight (Chassis Only)	Dimensions
95 kg 209 lb	L: 969.3mm, W: 650mm, H: 397.3mm (Excl handles) L: 38.2in, W: 25.6in, H: 15.6in (Excl handles)
Safety & EMC Regulations	
UL, CB, CCC, KC, RoHS (CN), FCC Class A, FDA, CE, IEC EN 60825-1 Class 3R Laser Product, IEC EN 62471-5 Risk Group 3, WEEE (UK)	

Accessories

Accessory	Part No.
Infrared Remote Control (Replacement)	118-678
Optional lens mount insert for selected competitor lenses	119-729

*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.

Downloads

PDF CAD Drawings	User Guides
AUTOCAD Drawings	User Guides (German)
STEP / IGS Drawings	User Guides (French)
Rigging Frame CAD Drawings Rigging	Laser Risk Group Document
Frame CAD Drawings	Important Information
Lens CAD Drawings	Control Protocol



Certificate Number 13629
ISO 9001

Specifications subject to change without notice. ©2020 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON
MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW,
GA. 30144
T: 770.420.1350 } F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, CHINA Rm A2301,Shaoyaoju 101 North Lane,Shi
Ao International Center,Chaoyang District,Beijing 100029,PR China
T: +86.10.58239771 | F: +86 10 58239770