# **BRONZE SUB**

# IN-ROOM, IN-CEILING, IN-WALL



## **BRONZE SUB**

#### IN-ROOM, IN-CEILING, IN-WALL

Triad's Bronze Sub's dynamic performance combines with discreet appearance in virtually any household setting.

Hear and feel deep, compelling bass with control and accuracy—experiencing impactful low frequencies which enhance and enrich movie soundtracks and music alike.

These subwoofers deliver unmatched performance with studio-grade drivers and sealed, internally braced enclosures. Long-throw woofers produce enhanced output and substantial impact with ultra-low distortion. Triad's subwoofers combine superior quality and efficiency, completing your soundscape with precision and power in any application or environment.

Triad offers two perfectly matched subwoofer amplifiers for these subwoofers—the RackAmp 300 and RackAmp 700. Both amplifiers have been engineered and tuned to bring out the best in these subwoofers and your system.

In an industry of generic, mass-produced products, Triad's handcrafted sealed-box enclosures deliver detailed acoustics and effortless playback, actualizing the artist's intent.

# **FEATURES**

- 10" ultra-low distortion, long throw woofer
- Passive subwoofer
- Internally braced cabinet design
- High power handling and high SPL output
- Fully-engineered, acoustic suspension premium MDF enclosure
- · Custom paint-matching service included

#### IN-ROOM

- Veneer finishes available
- Available in 4-ohm version

#### **IN-CEILING**

- Needs only 10" of ceiling space
- · Acoustiperf frameless metal grill
- Available in 4- or 8-ohm versions

#### IN-WALL

- Requires 6" of depth
- · AcoustiPerf frameless metal grill
- Available in 4- or 8-ohm versions




# BRONZE SUB IN-ROOM, IN-CEILING, IN-WALL

## **SPECIFICATIONS**

MATERIALS	IN-ROOM	IN-CEILING/10	IN-WALL/6
Woofer count	1	1	1
Woofer size	10" (25 cm)	(1) 10" (25 cm)	(1) 10" (25 cm)
Woofer type	Ultra-low distortion aluminum cone woofer	Long-excursion coated paper	Long-excursion coated paper
PERFORMANCE	IN-ROOM	IN-CEILING/10	IN-WALL/6
Power handling	300W	300W	300W
Frequency response (+/- 3 dB)	20 Hz - 200 Hz	20 Hz - 200 Hz	20 Hz - 200 Hz
F3 -3 dB	20 Hz	20 Hz	20 Hz
Impedance	4-ohm available	4- or 8-ohm available	4- or 8-ohm available
	'		
DIMENSIONS	IN-ROOM	IN-CEILING/10	IN-WALL/6
Cabinet specifications $(L \times W \times D)$	16 ½ × 13 ½ × 12 ½" (41.9 × 34.2 × 31.8 cm)	$13 \frac{1}{2} \times 13 \frac{1}{2} \times 9''$ (34.3 × 34.3 × 22.9 cm)	19 × 13 ½ × 6" (48.3 × 34.3 × 15.2 cm)
Hole cutout (L × W)	-	13 <sup>5</sup> / <sub>8</sub> × 13 <sup>5</sup> / <sub>8</sub> " (34.6 × 34.6 cm)	19 ¹/₅ × 13 ⁵/₅" (48.6 × 34.6 cm)
Frameless grill dimensions (L × W)	-	$14^{15}/_{16} \times 14^{15}/_{16}''$ (38 × 38 cm)	20 <sup>7</sup> / <sub>16</sub> × 14 <sup>15</sup> / <sub>16</sub> " (52 × 38 cm)
NCB size	-	G	V
Product weight (each)	45 lb (20.4 kg)	17 lb (7.7 kg)	28 lb (12.7 kg)
Shipping weight (each)	52 lb (23.1 kg)	20 lb (9.1 kg)	32 lb (14.5 kg)
PRODUCT NUMBERS	IN-ROOM	IN-CEILING/10	IN-WALL/6
1 Sub, 1 RackAmp 300 (4-ohm enclosure)	BSSIR-BDL1 (painted) BSSIR-BDL2 (veneer)	BSIC-BDL1 (painted)	BSSIW-BDL1 (painted)
2 Subs, 1 RackAmp 300 (8-ohm enclosure)	-	BSIC-BDL3	BSSIW-BDL3
1 Sub, 1 RackAmp 700 DSP (8-ohm enclosure)	-	BSIC-BDL2	BSSIW-BDL2
2 Subs, 1 RackAmp 700 DSP (8-ohm enclosures)	-	BSIC-BDL4	BSSIW-BDL4


## **DIMENSIONS**





IN-ROOM

# **IN-CEILING**



#### IN-WALL

