

DISTRIBUTED AUDIO SERIES 2

IW62 IN-WALL 6" OPEN BACK SPEAKER



Triad's IW62 speaker offers homeowners the refined, musical quality of Triad speakers for their whole home. This speaker is built around reinforced poly-mica woofers for superior bass and aimable Tetonon-dome tweeters for a full, natural sound.

Pivoting tweeter

With up to 10 degrees of movement, the pivoting tweeter delivers high-quality audio to the listener's position and offers flexible installation options.

Poly-mica woofer

Mica-infused polypropylene offers a strengthened cone material with increased rigidity and a high stiffness-to-weight ratio—while still maintaining the dampening properties of a traditional polypropylene woofer.

Voice matched

All Distributed Audio Series 2 speakers are voice matched—allowing homeowners to mix and match speakers within the series to meet the needs of each room, while providing identical tonal qualities throughout the home.

Magnetic mounting

Low-profile frameless grills attach to the speaker with hidden neodymium magnets for fast installation and a snug fit. Custom paint-matching is available.

Easy install

Using a tried-and-tested traditional Triad mounting system with reinforced threaded brass inserts, Distributed Audio Series speakers install in seconds and will stay snug to the mounting surface for the life of the system. High-quality spring clamps make connecting speaker wires simple and quick, while the magnetic frameless grill fits flush to the mounting surface with ease.

COMPONENTS

| | |
|--------------|-----------------|
| Tweeter size | 3/4" (19 mm) |
| Tweeter type | Tetonon® dome |
| Woofer size | 6 1/2" (165 mm) |
| Woofer type | Poly-mica |

PERFORMANCE

| | |
|-------------------------------|----------------|
| Maximum power | 125W |
| Recommended amp power | 5 - 125W |
| Maximum SPL | 110 dB |
| Impedance (nominal) | 8 ohm |
| Impedance (minimum) | 4.5 ohm |
| Sensitivity (dB @ 2.83V, 1 m) | 89 dB |
| Frequency response (+/-3 dB) | 51 Hz - 22 kHz |
| Dispersion (8K/-6dB) | 105° H × 90° V |

DIMENSIONS

| | |
|------------------------------------|--|
| Cabinet specifications (H × W × D) | 14 3/16 × 8 7/16 × 3 1/4" (36.1 × 21.5 × 8.1 cm) |
| Hole cut out (H × W) | 13 1/8 × 7 3/8" (33.3 × 18.7 cm) |
| Frameless grill dimensions (H × W) | 14 5/16 × 8 9/16" (36.4 × 21.7 cm) |
| Mounting depth | 3 1/8" (7.8 cm) |
| Product weight (each) | 4.5 lb (2.05 kg) |
| Grill material | Metal Perf-Frameless |
| New construction bracket size | NCBIW6 |

PRODUCT NUMBERS

| | |
|--------------------------|---------------------------|
| Speaker | TS-IW62 |
| Replacement grill | TS-GRLIW6 |
| New construction bracket | TS-NCBIW6 |