



WattBox 250-Series Wi-Fi Surge Protector

The WattBox 250 IPW series is a compact Wi-Fi WattBox with individually controlled outlets, professional-grade surge protection, and the option for wired connectivity. The WattBox 250 is the only 2-outlet individually controlled surge protector that supports OvrC, the industry's #1 remote management platform. With its affordable price point and the power of OvrC, putting this WattBox on every job will save you time and money.

Thanks to its small size and wireless capability, you can power and control everything from digital signage or a smart TV to video conferencing equipment. The only limit to where you can put this WattBox to enjoy its incredible benefits is your own creativity.



Three Lines of Defense

Controlled & Metered Outlets

Control each outlet independently for advanced troubleshooting and the ability to reboot single devices without entire system disruption. Schedule precise outlet power cycles and remote system start-up or create a customized sequence via OvrC to ensure your client's system gets back up and running in no time.

Small & Mighty

The compact, Wi-Fi enabled WattBox 250 Series offers control and troubleshooting capabilities. Two individually controlled outlets allow you to create precise schedules and power cycles. Just pair your WattBox with a control system, and your clients can do it themselves.

Upgrade Your Installs with IP Power

With WattBox, you get access to individually metered and controlled outlets, advanced control system integration, and access to OvrC remote management. Together, WattBox + OvrC support every part of your install and help avoid using multiple remote management platforms.

The Power of WattBox + OvrC

WattBox and OvrC work together to help you remotely troubleshoot and, solve problems and limit service calls – all for free. Through the easy-to-use OvrC desktop or mobile app, you're able to reboot devices and quickly fix common issues to keep your customers' systems running smoothly.

	250 IPW Series
Models	WB-250I-IPW-2
Number of Outlet Options	2
# of IP Outlet Control	2
Ethernet Connectivity	●
WiFi Enablement	●
Product Size	169*36.1*117.5 (mm)
AC Input Connection	IEC 60320 C14
Line Voltage	220` 240VAC, 50/60 Hz
Circuit Breaker/Fuse Rating	10A, 250VAC
Power Rating	1440W
Surge Component	Metal Oxide Varistor (MOV)
Current Rating	6A
Voltage Protection Rating	L-N 1.2kV, L-E 2.3kV, N-E 1.9kV
Surge Joule Rating	1260J
Safe Voltage	●
Certifications	CE Certified RCM Certified CB Safety Certified
Detachable IEC Power Cord	●
Remote Firmware Upgrades	●
Self-healing Auto-Reboot	●
Scheduled Power Cycles	●
Remote Management	●
Mobile End-User App	●
Local Control API	●

