









	Custom Series											
Product	A Height w/ Casters"	B Height w/o Casters"	C Usable Rack Space Height	D Width	F Width Including Side Panels	G Front/ Rear Door Depth	H Depth w/ Front & Rear Doors	J Usable Depth	Overall Depth	Construction	UL Certified	Max Load Weight
SR-CUSTOM-21U-20IN	43.25" (109.8cm)	40.25" (102.2cm)	36.75" (93.3cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	23.31" (59.2cm)	20" (50.8cm)	20.16" (51.2cm)	Steel w/ Black Powder Coat	<	1000 lbs (453.5kg)
SR-CUSTOM-21U-24IN	43.25" (109.8cm)	40.25" (102.2cm)	36.75" (93.3cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	27.31" (69.4cm)	24" (61cm)	24.16" (61.4cm)	Steel w/ Black Powder Coat	>	1000 lbs (453.5kg)
SR-CUSTOM-27U-20IN	53.75" (136.5cm)	50.75" (128.9cm)	47.25" (120cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	23.31" (59.2cm)	20" (50.8cm)	20.16" (51.2cm)	Steel w/ Black Powder Coat	>	1000 lbs (453.5kg)
SR-CUSTOM-27U-24IN	53.75" (136.5cm)	50.75" (128.9cm)	47.25" (120cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	27.31" (69.4cm)	24" (61cm)	24.16" (61.4cm)	Steel w/ Black Powder Coat	>	1000 lbs (453.5kg)
SR-CUSTOM-32U-20IN	62.5" (158.8cm)	59.5" (151.1cm)	56" (142.2cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	23.31" (59.2cm)	20" (50.8cm)	20.16" (51.2cm)	Steel w/ Black Powder Coat	\	1000 lbs (453.5kg)
SR-CUSTOM-32U-24IN	62.5" (158.8cm)	59.5" (151.1cm)	56" (142.2cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	27.31" (69.4cm)	24" (61cm)	24.16" (61.4cm)	Steel w/ Black Powder Coat	>	1000 lbs (453.5kg)
SR-CUSTOM-37U-20IN	71.25" (181cm)	68.25" (173.4cm)	64.75" (164.5cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	23.31" (59.2cm)	20" (50.8cm)	20.16" (51.2cm)	Steel w/ Black Powder Coat	<	1000 lbs (453.5kg)
SR-CUSTOM-37U-24IN	71.25" (181cm)	68.25" (173.4cm)	64.75" (164.5cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	27.31" (69.4cm)	24" (61cm)	24.16" (61.4cm)	Steel w/ Black Powder Coat	<	1000 lbs (453.5kg)
SR-CUSTOM-42U-20IN	79.9" (203cm)	76.9" (195.3cm)	73.5" (186.7cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	23.31" (59.2cm)	20" (50.8cm)	20.16" (51.2cm)	Steel w/ Black Powder Coat	>	1000 lbs (453.5kg)
SR-CUSTOM-42U-24IN	79.9" (203cm)	76.9" (195.3cm)	73.5" (186.7cm)	19.77" (50.2cm)	21.02" (53.4cm)	1.58" (4cm)	27.31" (69.4cm)	24" (61cm)	24.16" (61.4cm)	Steel w/ Black Powder Coat	/	1000 lbs (453.5kg)

	Signature Series											
Product	A Height w/ Casters"	B Height w/o Casters"	C Usable Rack Space Height	D Width	F Width Including Side Panels	G Front/ Rear Door Depth	H Depth w/ Front & Rear Doors	J Usable Depth	Overall Depth	Construction	UL Certified	Max Load Weight
SR-AV-CAB-22U-25IN	44.4" (112.8cm)	42" (106.7cm)	38.5" (97.8cm)	23.5" (59.7cm)	23.5" (59.7cm)	-	25" (63.5cm)	22.5" (57.2cm)	25" (63.5cm)	Steel w/ Black Powder Coat	~	2200lbs. (997.9kg)
SR-AV-CAB-32U-25IN	61.9" (157.2cm)	60" (152.4cm)	56" (142.2cm)	23.5" (59.7cm)	23.5" (59.7cm)	-	25" (63.5cm)	22.5" (57.2cm)	25" (63.5cm)	Steel w/ Black Powder Coat	~	2200lbs. (997.9kg)
SR-AV-CAB-42U-25IN	79.4" (201.7cm)	77" (195.6cm)	73.5" (186.7cm)	23.5" (59.7cm)	23.5" (59.7cm)	-	25" (63.5cm)	22.5" (57.2cm)	25" (63.5cm)	Steel w/ Black Powder Coat	~	2200lbs. (997.9kg)
SR-AV-CAB-42U-30IN	79.4" (201.7cm)	77" (195.6cm)	73.5" (186.7cm)	23.5" (59.7cm)	23.5" (59.7cm)	-	34" (86.4cm)	31.5" (80cm)	34" (86.4cm)	Steel w/ Black Powder Coat	~	2200lbs. (997.9kg)

	FS Series											
Product	A Height w/ Casters"	B Height w/o Casters"	C Usable Rack Space Height	D Width	F Width Including Side Panels	G Front/ Rear Door Depth	H Depth w/ Front & Rear Doors	J Usable Depth	Overall Depth	Construction	UL Certified	Max Load Weight
SR-FS-SYSTEM-DC-15U	34" (86.4cm)	30.25" (76.8cm)	26.25" (66.7cm)	"21.1"" (53.6cm)	21.1" (53.6cm)	-	23.25" (59.1cm)	18.25" (46.4cm)	23.25" (59.1cm)	Steel w/ Black Powder Coat	-	750lbs. (340.1kg)
SR-FS-SYSTEM-DC-21U	44.5" (113cm)	40.75" (103.5cm)	36.75" (93.3cm)	"21.1"" (53.6cm)	21.1" (53.6cm)	-	23.25" (59.1cm)	18.25" (46.4cm)	23.25" (59.1cm)	Steel w/ Black Powder Coat	-	750lbs. (340.1kg)
SR-FS-SYSTEM-DC-27U	55" (139.7cm)	51.25" (130.2cm)	47.25" (120cm)	"21.1"" (53.6cm)	21.1" (53.6cm)	-	23.25" (59.1cm)	18.25" (46.4cm)	23.25" (59.1cm)	Steel w/ Black Powder Coat	-	750lbs. (340.1kg)
SR-FS-SYSTEM-DC-35U	67.5" (171.5cm)	64.6" (164.1cm)	61.25" (155.6cm)	21.1" (53.6cm)	21.1" (53.6cm)	-	23.1" (58.7cm)	18.25" (46.4cm)	23.1" (58.7cm)	Steel w/ Black Powder Coat	-	1000lbs (453.6kg)
SR-FS-SYSTEM-DC-42U	79.7" (202.4cm)	76.8" (195.1cm)	73.5" (186.7cm)	21.1" (53.6cm)	"21.1"" (53.6cm)"	-	23.1" (58.7cm)	18.25" (46.4cm)	23.1" (58.7cm)	Steel w/ Black Powder Coat	-	1000lbs (453.6kg)

	IT Datacom Series											
Product	A Height w/ Casters"	B Height w/o Casters"	C Usable Rack Space Height	D Width	F Width Including Side Panels	G Front/ Rear Door Depth	H Depth w/ Front & Rear Doors	J Usable Depth	Overall Depth	Construction	UL Certified	Max Load Weight
SR-IT-CAB-42U-30IN	78.75" (200cm)	76" (193cm)	73.5" (186.7cm)	23.6" (59.9cm)	23.6" (59.9cm)	-	34" (86.4cm)	31.5" (80cm)	34" (86.4cm)	Steel w/ Black Powder Coat	~	2200lbs. (997.9kg)
SR-IT-CAB-42U-40IN	78.75" (200cm)	76" (193cm)	73.5" (186.7cm)	23.6" (59.9cm)	23.6" (59.9cm)	-	42" (106.7cm)	39.4" (100.1cm)	42" (106.7cm)	Steel w/ Black Powder Coat	~	2200lbs. (997.9kg)

	Contractor Series											
Product	A Height w/ Casters"	B Height w/o Casters"	C Usable Rack Space Height	D Width	F Width Including Side Panels	G Front/ Rear Door Depth	H Depth w/ Front & Rear Doors	J Usable Depth	Overall Depth	Construction	UL Certified	Max Load Weight
SR-CS-RACK-12U	27.8" (70.6cm)	23.8" (60.5cm)	21" (53.3cm)	20" (50.8cm)	20" (50.8cm)	-	18.2" (46.2cm)	18.2" (46.2cm)	18.2" (46.2cm)	Steel w/ Black Powder Coat	✓	"600lbs (272.2kg)
SR-CS-RACK-16U	34.8" (88.4cm)	30.9" (78.5cm)	28" (71.1cm)	20" (50.8cm)	20" (50.8cm)	-	18.2" (46.2cm)	18.2" (46.2cm)	18.2" (46.2cm)	Steel w/ Black Powder Coat	~	"600lbs (272.2kg)
SR-CS-RACK-21U	43.5" (110.5cm)	39.6" (100.6cm)	37" (94cm)	20" (50.8cm)	20" (50.8cm)	-	18.2" (46.2cm)	18.2" (46.2cm)	18.2" (46.2cm)	Steel w/ Black Powder Coat	~	"600lbs (272.2kg)

 $Not all \ products \ are \ available \ in \ all \ regions. \ Please \ check \ with \ your \ local \ sales \ representative \ for \ availability.$